


**BESCHREIBUNG**

- > RG 174/U is a coaxial cable with stranded copper clad steel wire and with a tinned copper wire braid shield.
- > The material specification of the outer jacket is classified as Low Smoke Zero Halogen (LSZH) material.



**BESTELLUNG**

Modell	Produkt Nr
--------	------------

**SPEZIFIKATIONEN**

Elektrisch DE	
Geschwindigkeitsfaktor	0.66
Kapazität	100 - 3 pF/m
Impedanz	50 Ω
Mechanisch DE	
Innerer Leiter Dia / Matl	0.48 mm dia. (7 x 0.160 mm) Copper clad steel wire
Äußerleiter Dia.	1.8 mm / 0.07 in.
Dämm Material	1.5 mm dia. PE
Geflochtenes Material	Cu-verzinkt
Mindest. Biegungsradius	21 mm / 0.83 in.
Gewicht	0.011 kg / 0.02 lb
Jacke Dia / Matl	dia. 0.15 mm LSZH
Geflochtene Abdeckung	85 %
Umwelt	
Betriebstemperaturbereich	-25°C to +60°C

**ADDITIONAL DATA**

ATTENUATION		
FREQUENCY	[dB/100m]	Max. HF-power/W
150 MHz	32.3	210
450 MHz	57.8	
900 MHz	83.6	
1400 MHz	106.1	
1800 MHz	122.1	
2200 MHz	137.0	
2500 MHz	147.2	
3000 MHz	165.7	