



NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
 1. BRASS PER QQ-B-626
 2. BRASS PER QQ-B-613
 3. NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
 4. PHOSPHOR BRONZE PER QQ-B-750
 5. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
 6. TEFLON MIL-P-19468

DIMENSIONS ARE IN MILLIMETERS			
UNLESS OTHERWISE SPECIFIED TOLERANCES			
0.5-6	=	±0.2	
6-30	=	±0.4	
30-120	=	±0.6	
120-315	=	±1	
315-1000	=	±1.6	
1000-2000	=	±2.4	

NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.
7	HEX NUT			1	HN19-5/8-24X31
6	LOCK WASHER			1	LW-19/16X06
5	GASKET	SILICONE	RED	1	GS-20/16X15
4	BODY			1	N7910-4
3	CONTACT PIN			1	N7900-3
2	INSULATOR		NATURAL	1	N7900-2T-50-B
1	HOUSING			1	N7910-1

PART NO.	
APPROVED	DATE 01-26-99'
CHECKED	DATE 01-26-99'
DRAWN	DATE 01-26-99'

KAI JACK INDUSTRIAL CO., LTD. TAINAN TAIWAN R.O.C.	
TITLE	N FEMALE TO FEMALE BULKHEAD ADAPTOR
DRAWING NO.	KJ-N7471A1-NT3G-50
FILE NO.	F:\DWG\N\7471A1\50\NT3G

參考
2000. 12. 14
設計部

88DFR472