

# Duplex Filter for the 150 MHz Band

# DESCRIPTION

- High power base station duplex filter for the 140 175 MHz range.
- > The use of large ø250 mm cavities means a high Q, resulting in a very narrow duplex spacing.
- > The large dimensions also mean a high power rating.
- > Unloaded Q of a single cavity is approx. 8000.
- > High frequency stability on temperature and power.
- > Mounted on 19" brackets.



### SPECIFICATIONS

Electrical	
Model	DPF 2/33-250-WM
Frequency	140 - 175 MHz
Max. Input Power	300 W @ 1.5 dB IL 150 W @ 3.0 dB IL
Insertion Loss	250 kHz @ < 2.0 dB 500 kHz @ < 1.5 dB 750 kHz @ < 1.0 dB
Tx Noise Suppression on Rx-Freq. / Rx Isolation on Tx-Freq.	250 kHz @ > 80 dB 500 kHz @ > 90 dB 750 kHz @ > 100 dB
Mechanical	
Connection(s)	N(f)
Dimensions	510 x 750 x 600 mm / 20.07 x 29.52 x 23.62 in.
Weight	Approx. 19.2 kg / 42.33 lb.
Environmental	
Operating Temperature Range	-30°C to +60°C
Frequency Stability	1.5 ppm/° C (approx.)

#### U NG

Model	Product No.
DPF 2/33-250-WM	200001877

## TYPICAL RESPONSE CURVES FOR 500 KHZ DUPLEX

